


Berridge Tee-Lock Panel Load Chart

OPEN FRAMING



Tee-Lock Section Properties Based on 24 Gauge 40			
K.S.I.			
	I_x (in ⁴ /ft)	M_A (ft*lbs/ft)	V_A (lbs/ft)
Positive Bending	0.1525	184.65	990
Negative Bending	0.1031	161.33	990

NOTES:

- 1) Tee-Lock Panel with 16 GA Tee-Lock Clip.
- 2) Values based on 1996 edition of AISI and good engineering practice.

Open Framing on 16 ga Steel Support (Galvalume Substrate)						
Gauge of Panel	Spacing (in)	Clip Type	Fastener	Fastener Quantity	Allowable (psf)	Ultimate (psf)
24	30	Fixed Clip	#12-14 Fenderhead T-3 SD	2	67.68	135.35
24	36	Fixed Clip	#12-14 Fenderhead T-3 SD	2	60.90	121.80
24	42	Fixed Clip	#12-14 Fenderhead T-3 SD	2	54.13	108.25
24	48	Fixed Clip	#12-14 Fenderhead T-3 SD	2	47.35	94.70
24	54	Fixed Clip	#12-14 Fenderhead T-3 SD	2	40.58	81.15
24	60	Fixed Clip	#12-14 Fenderhead T-3 SD	2	33.80	67.60
24	60	Tee-Rib	#12-14 Fenderhead T-3 SD	2	140.50	281.00

NOTES:

- 1) Fenderhead fasteners to be without washer.
- 2) All test results determined through ASTM E1592 testing standards.



CORPORATE HEADQUARTERS

2610 Harry Wurzbach Road
 San Antonio, TX 78209
 (800) 669-0009
 www.Berridge.com